



DAESAN Lever Hoist

Product Specification | Revision 2026.10 | Rev 1.0

Factual product reference media follows the technical specification.

DAESAN NDM manual lever hoists from 0.8 t to 12 t. Standard supplied lift is 3 m.

Selection notes

- Specify capacity, lift and attachment arrangement.
- Do not apply the permit scope to the 12 t variant.

Technical specifications

Model	Capacity (t)	Falls	Std lift (m)	Ref lift (m)	Load chain (mm)	Ref mass (kg)	A	B	C	D	E	F	G	Pull effort (kgf)
NDM08	0.8	1	3	1.5	6.3	7	155.5	121	329.5	273	102	38	25	30
NDM15	1.5	1	3	1.5	7.1	10.5	168.5	141.5	379	386	107	45	28	30
NDM20	2	1	3	1.5	7.1	11	168.5	141.5	395	386	107	45	30	40
NDM30	3	1	3	1.5	9	17.5	201	172.5	465	386	117	52	38	37
NDM60	6	2	3	1.5	9	29	201	241	615	386	117	70	46	38
NDM90	9	3	3	1.5	9	56	201	349	775	386	117	131	57	39
NDM120	12	4	3	1.5	9	74	201	349	880	386	117	131	79	40

Standards & Documentation

SANS 1636:2007. SABS Permit 11894/18657. Covered capacities: 0.8, 1.5, 2, 3, 6 and 9 t. The 12 t configuration is outside the current evidenced certificate scope.

Request a Quote | Availability confirmed at quotation | info@coopergroup.co.za | +27 11 493 4355

DAESAN Lever Hoist

